

AMPLIFIER SPECS CHART

Model Numbers	Output Power Rating/Channel	Channels	Frequency Response*	Distortion**	Speaker Outputs	AC Line Draw***	Dimensions	Product Weight	
BP460	60W	1	20 Hz to 20 kHz	2% Max	8-ohm/25V, 16-ohm, 25VCT, 70V	180W	15-1/4" W x 3-1/2" H x 8-1/4" D	17 lb.	
C10	10W	1	70 Hz to 16 kHz	1% Max	70V, 25V, 16-ohm, 8-ohm, 4-ohm	38W	11-3/8" W x 2-7/8" H x 7-3/8" D	5 lb.	
C10MDH	20W							6 lb.	
C35	35W	1	70 Hz to 16 kHz - Transformer; 20 Hz to 20 kHz - Direct	1% Max	70V, 25V, 16-ohm, 4-ohm direct 8-ohm on C35 and C60	148W	14-1/2" W x 3-3/4" H x 11" D	15 lb.	
C60	60W							17 lb.	
C100	100W							220W	19 lb.
GA2	1.5W	1	200 Hz to 15 kHz	2% Max	8- & 600-ohm	4W	5-1/2" W x 4-1/8" H x 2-1/4" D	2 lb.	
GA6A	6W	1	30 Hz to 12 kHz	2% Max	70V, 25V, 8-ohm	16W	8-1/2" W x 2-3/4" H x 6" D	5 lb.	
GS35	35W	1	65 Hz to 20 kHz - Transformer; 20 Hz to 20 kHz - Direct	0.5% Max	70V, 25V, 25VCT, 8-ohm, 4-ohm direct	2.2A	16-1/2" W x 3-1/2" H x 13-1/2" D	17 lb.	
GS60	60W							20 lb.	
GS100	100W							23 lb.	
GS150	150W							29 lb.	
GS250	250W							30 lb.	
HTA125A	125W	1	20 Hz to 20 kHz	0.5% Max	70V, 25VCT, 25V, 8-ohm, 4-ohm	260W	19" W x 5-1/4" H x 11" D	36 lb.	
HTA250A	250W					520W		50 lb.	
M300	300/600W	2	20 Hz to 20 kHz	0.5% Max	4- to 8-ohm (2 channel mode); 70V (1 channel mode)	12A	17" W x 9-1/2" H x 18-1/2" D (not including brackets)	41 lb.	
M450	450/900W	or						44 lb.	
M600	600/1200W	1						46 lb.	
MT250D	250W	1	20 Hz to 20 kHz	2% Max	100V, 70V, 25V, 12.5V, 8-ohm	620W	19" W x 13" H x 5-1/4" D	49 lb.	
PM3180	100W 60W 20W	3	70 Hz to 20 kHz - Trans (Amp 1 & 2); 70 Hz to 15 kHz - Trans (Amp 3); 20 Hz to 20 kHz - Direct (Amp 1 & 2); 20 Hz to 15 kHz - Direct (Amp 3)	0.5% - Amp 1 & 2; 1% - Amp 3 (Max)	70V, 25V, 8-ohm, 4-ohm direct	430W	17" W x 5-1/2" H x 12-1/2" D	38 lb.	
TPU15A	15W	1	70 Hz to 12 kHz	2% Max	70V, 25V, 8-ohm	48W	11" W x 2-3/4" H x 2-3/8" D	4 lb.	
TPU35B	35W							12 lb.	
TPU60B	60W							15 lb.	
TPU100B	100W							18 lb.	
TPU250	250W							28 lb.	
V35	35W	1	70 Hz to 15 kHz	1% Max	70V, 25V, 25VCT, 16-ohm	0.75A	14-1/4" W x 8-3/8" H x 3-5/8" D	24 lb.	
V60	60W							28 lb.	
V100	100W							32 lb.	
V150	150W							35 lb.	
V250	250W							40 lb.	
WV100	100W	1	45 Hz to 20 kHz - Transformer; 20 Hz to 20 kHz - Direct	0.5% - Transformer; 0.1% - Direct (Max)	70V, 25V, 8-ohm, 4-ohm direct	2.0A	17" W x 3-1/2" H x 14-3/4" D	27 lb.	
WV150	150W							29 lb.	
WV250	250W							5.5A	28 lb.
X300	300W	2	20 Hz to 20 kHz	0.5% Max	70V direct	12A	17" W x 3-1/2" H x 18-1/4" D (not including brackets)	41 lb.	
X450	450W							15A	44 lb.
X600	600W							20A	46 lb.

* @ -20dB FRP Transformer output;
@ FRP for Direct outputs

** Bandwidth limited to frequency response

*** FRP @ 120V AC line voltage

Specifications subject to change without notice.