

BCAM Series Wired Square Clock (V4.1)

Features:

- Available in 9" (22.8cm), and 12" (30.4 cm) dial sizes
- Offered in a stylish ABS case
- Multiple power options
 - Offered in 110VAC, 230VAC and 24VAC/VDC models
- Provided with mounting hardware for easy installation
- Hour, minute, and second hands
- Quick correction for time change (max. 5 minutes when used with digital communication protocol)
- Microprocessor based movement
- Side molded, polycarbonate crystal

Highlights:

- Designed and Produced in the United States of America
- Automatically recognizes many wired time data protocols:
 - 2-wire digital communication system (24V clock only)
 - 3-wire digital communication system
 - Sync-wire 59 minute correction
 - Various Sync-wire 58 minute correction formats
 - National Time/Rauland correction
- Correctly interprets time data protocols even if the **signal** wire polarity is switched.
- Built-in self-diagnostic mode:
 - Communication Protocol Verification
 - Time since the last synchronization signal was received
 - Hand position error detection
- Custom Color Cases available (minimum quantity 25)



BCAM Series Wired Square Clock (V4.1)

Specifications:

Case Material:

ABS

Case Color:

Standard black or white back case, metallic gray front rim (custom colors available)

Dial Face:

12 or 24 (military) hour standard
Specialty dials available

Dial Material:

Durable polystyrene

Crystal Material:

Shatter-proof, side-molded, transparent polycarbonate

Voltage Input:

7-28 VDC/VAC 50/60 Hz (24V model)
85 - 130 VAC 50/60 Hz (110V model)
180 - 260 VAC 50/60 Hz (230V model)

Average Current Consumption:

35 mA @ 24VAC
25 mA @ 110VAC
15 mA @ 230VAC

Hand tolerance:

Minute hand: +/- 1/4 minute
Second hand: +/- 1/2 second

Temperature range:

Operating: 32°F - 113°F (0°C - 45°C)
Shelf: 5°F - 167°F (-15°C - 75°C)


Compliance:

UL, cUL listed, CE Compliances: EMC, LVD




Ordering Information:

BCAM Series Wired Square Clock: BCAM-4XS-XXS-X-XX



Double Mount Pole: BCAB-4XD-XXS-0



Note: Purchasing double mounted square analog clocks will require two clocks using the clock part number and one double mount pole using the part number above.


Examples:

BCAM-4WS-09S-4: Bogen Analog, Wired BCAM, 9" Square, 24V, Surface Wall Mount, White Case with Metallic Gray Rim, Supports: 2-Wire Digital & Sync Wire Protocols

BCAM-4BS-12S-1: Bogen Analog, Wired BCAM, 12" Square, 110 VAC, Surface Wall Mount, Mineral Black Case with Metallic Gray Rim, Supports: Sync Wire Protocols

BCAM Series Wired Square Clock (V4.1)

Bogen Square Analog Clock Dimensions



| | 9" Square | 12" Square |
|---|--|--|
| Clock Size: | W = 9.79" (24.9cm) W2 = 8.97" (22.8cm) D = 2.44" (6.2cm) D2 = 1.34" (3.4cm) | W = 12.76" (32.4cm) W2 = 11.94" (30.3cm) D = 2.44" (6.2cm) D2 = 1.34" (3.4cm) |
| Shipping Weight: | 3.0lbs (1.81kg) | 4.0lbs (1.81kg) |
| Double/Dual Mount Dimensions: | W3 = 6.56" (16.7cm) D3 = 4.93" (12.5cm) | W3 = 6.56" (16.7cm) D3 = 4.93" (12.5cm) |
| Adjustable Pole Height for standard pole*: | L3 = 18.32" (46.5cm) | L = 21.12" (53.6cm) L = 19.35" (49.1cm) |
| Shortened Pole Height: | L = 12.38" (31.4cm) | L = 15.50" (39.3cm) |

***Standard** pole refers to part number BCAB-4GD-00S-0


****Shortened** pole (ceiling mount only) refers to part number BCAB-4GD-01S-0

BCAM Series Wired Square Clock (V4.1)


Hand & Dial Options




Standard Hands




Specialty Hands 1




Specialty Hands 2




Specialty Hands 3




Standard Dial




Dial M
(Military 24 Hours)




Dial A




Dial B




Dial C




Dial D




Dial E



Dial F



Dial G



Dial Z

Specialty Hands 1-3 & Specialty Dials A-Z are offered at an additional cost.

For more information please contact your Bogen Representative.