

LB6

ALL-ENVIRONMENT OUTDOOR SPEAKER



DESIGNED TO ENTERTAIN

FULL RANGE, ALL-ENVIRONMENT BRACKET-MOUNT SPEAKER

The **NEAR**® LB6 speaker is elegantly designed, rugged to the extreme and a snap to install. The LB6 employs a **NEAR** exclusive “lever bracket” mount combined with a perfect-fit, totally waterproof input connector. This mounting system minimizes installation effort and reduces “ladder time” to improve installation safety. The LB6 utilizes MDT/MLS woofers with 1” titanium inverted dome tweeters for timbre consistency across the range to allow for complete system design flexibility. The LB6 enclosure is color-through, mica-loaded polypropylene with color-matched stainless steel grille. Water-shedding and dust-protecting hydrophobic fabric prevents ingress of fine debris.



The LB Series speakers quickly and easily slide into slots in the clamp module, with knobs and bracket pre-attached to the speaker. The knobs are also oversized for easier grip and better control during installation. The speaker assembly comes with a pre-terminated waterproof plug-in connector that makes installation a breeze.

NEAR®
NOTHING COMES CLOSER

NEAR is a Division of Bogen Communications, Inc.

LB6

ALL-ENVIRONMENT OUTDOOR BRACKET-MOUNT SPEAKER

FEATURES

- Purpose-built to be extremely durable in all weather conditions
- Anodized metal-alloy speaker cones (MDT) are extremely stable
- Coincident driver configuration for symmetrical dispersion in any orientation
- Waterproof (IP68) input connector (included) eliminates long-term connection problems
- MLS Ferrofluid voice coil centering system
- Fluid-sealed gap eliminates corrosion in magnet
- Dual-layer voice coil with inside and outside windings for ultra-low distortion
- Mineral-filled polypropylene cabinet for durability and rigidity
- Advanced polymer cone surrounds resist UV rays, chlorine, fertilizer and salt spray
- Heavy-gauge, powder-coated stainless steel mounting bracket with unique (patent-pending) cast aluminum lever-mount clamp
- 70V transformer version available (LB6T) for use with the NEAR 6XL power amplifier or equivalent
- Specially developed hydrophobic fabric port covers prevent entry of water, debris and small creatures
- Colors: Available in black and white (both paintable)



SPECIFICATIONS

Frequency Response	48Hz to 19kHz, +/-2.5dB
Sensitivity (1W/1m)	88dB
Dispersion.....	Minimum 120 Degrees, Horizontal & Vertical
Power Requirements (LB6 @8 ohms).....	Up to 150 Watts (Ave); 600W Peak
Power Requirements (LB6T @70V)	64W, 32W, 16W, 8W, 4W or 8 ohms
Dimensions.....	8.58"W x 15.75"H x 8.9"D; 21.8cm W x 40cm H x 22.6cm D
Product Weight (w/mounting yoke & clamp).....	LB6: 11lbs/4.53kgs; LB6T: 12lbs/5.44kgs
Maximum SPL @1m (1/2 space).....	110dB
Input Terminations	Waterproof Plug-In Connector (IP68 Rating)
Environmental	Engineered to Meet or Exceed Mil-Std-810 (Humidity, Salt Air, Heat, Cold, Immersion); IEC IP 66

SPEAKER COMPLEMENT:

- (1) 6.5" Metal-Alloy Diaphragm Woofer, MLS Voice Coil Guidance, UV and Chemical-Resistant Rubber Surround
- (1) 1.1" Metal-Alloy Diaphragm Tweeter, Ferrofluid Damping, UV and Chemical-Resistant Rubber Surround, Corrosion-Resistant Magnet Assembly

NEAR[®]
NOTHING COMES CLOSER

www.bogen.com

NEAR is a Division of Bogen Communications, Inc.

© 2013-2016, Specifications are subject to change.