



S810 VoIP Ceiling Talkback Speaker

Model S810QIPPG8U



Description Bogen's Quantum Multicom IP Communications System has been enhanced to support PoE VoIP Speakers. The S810 VoIP Ceiling Talkback Speaker Assemblies consist of an 8" Cone Speaker pre-assembled onto a 13" steel ceiling grille painted with bright white enamel. All Quantum VoIP Speakers have been designed to facilitate rapid and efficient deployment using existing network PoE ports that are 802.3af compliant. These VoIP Speakers facilitate ease of placement wherever needed within a facility.

- | | |
|--|---|
| <p>Features</p> <ul style="list-style-type: none"> • PoE - no local power required • IEEE 802.3af compliant • Five software adjustable SPL levels available 4W, 2W, 1W, 1/2W, 1/4W • DHCP deployment for easy install • Further supports hybrid-IP approach • Pre-assembled for faster installation • Can be configured as one of two (2) new Quantum station types: talkback speaker only or talkback speaker with call-switch • An input is provided to connect an analog Call Switch | <ul style="list-style-type: none"> • Designed specifically for Bogen Quantum Multicom IP • 10 oz. magnet weights help produce high-quality sound • Supports receiving audio distribution via Multicast RTP and G.711 codec • Engineered to reduce network traffic by playing alarms / tones / announcements locally in the speaker • Supports DHCP or Static IP configuration • No licensing fees |
|--|---|

NOTE: The Privacy feature on Call-Switches w/ Privacy is not supported

Technical Specifications

Connectors: RJ45 - Network Interface
3-Pin 0.5 mm pluggable wire terminal for analog Call Switch

SPL: 90dB at 1/4W power level
93dB at 1/2W power level
96dB at 1W power level
99dB at 2W power level
102dB at 4W power level

Speaker: 8-inch with 10 oz. magnet

Dimensions: 13" dia. x 3-1/2" deep

Weight: 3 lbs.

Certifications: FCC Class A


SYSTEM CAPACITY: A combined maximum of 50 Quantum VoIP ceiling/wall baffle speakers can be installed in a single Quantum facility, regardless of the number of nodes/processors.

Additional Hardware Accessories

RE84
Recessed
Enclosure



TB8
Tile
Bridge



MR8
Mounting
Ring



Architect & Engineer Specifications

For Architect and Engineer Specifications please refer to:
<http://www.bogen-es.com/quantum/documentation/docs/QuantumAEs.doc>

BOGEN[®]
COMMUNICATIONS, INC.
www.bogen.com